

DS-PT1-WB Wireless Tag Reader

114-252

DS-PT1-WB wireless tag reader can connect to wireless security control panel for arming/disarming. It can also notice alarm by indicator and buzzer.



Key Features

- 433MHz two-way wireless communication
- AES-128 encryption
- LED display, show the different feedbacks with easy understanding
- Operation: Stay arm/away arm/disarm by areas
- Arming process with fault confirm, more secure
- Patrol tag check in
- Front and rear panel tamper-proof

Specification

Model		DS-PT1-WB
RF	Frequency	433MHz
	RF method	Two way communication
	RF encryption	AES-128
	Modulation	2GFSK
	RF distance	900m (open area)
Interface & component	TAMPER switch	1
	Power switch	Power on/off
	Indicator	5, area(blue), fault(orange), arm(blue), disarm(green), alarm(red), signal(red/green)
	Buzzer	Prompt for tag operation, entry/exit delay and tamper/alarm
Electrical & battery	Power Consumption	Quiescent current: 110 uA Max current: 292mA Voltage: 1.5 VDC
	Battery type	Three AA batteries
	Battery life span	2 years (swipe tag 10 times per day)
Others	Operation humidity	10% to 90% (no condensing)
	Operation temperature	-10°C to +55°C (-4°F to +122°F)
	Dimension (W × H × D)	75*124*21 mm
	Weight	176g (with battery)
	Color	white
	Installation	Wall mounting
Approvals	FCC	Supported
	CE/CB	Supported
	RCM	Supported
	Rohs/Reach/WEEE	Supported

ORDERING INFORMATION

114-252

Hikvision AX PRO Series Tag Reader



Innovative Electronic Solutions
www.ness.com.au



NSW Ph 02 8825 9222
sales@ness.com.au

VIC Ph 03 9875 6400
nessmelb@ness.com.au

QLD Ph 07 3399 4910
nessbris@ness.com.au

WA Ph 08 9328 2511
nessper@ness.com.au

SA Ph 08 8152 0000
adelaide@ness.com.au