

DS-PS1-B
Wired Sounder

114-508



The wired sounder is used to connect to wired control panel, by using 12v output voltage from panel, the sounder can alarm up to 105dB sound. The sounder can be used both internal or external, the LED flash and the sounder indication can be configured separately.

- Sound Decibel: 105dB at 30cm
- IP54 protective level
- Sound and LED flash indication separately
- Easy installation with new designed structure

▪ Specification

	Model	DS-PS1-B
Electrical characteristics	Power supply	8 to 16 VDC, Max. 0.22A
	Operating humidity	10% to 90%
	Operating temperature	-20°C to +60°C
	Power consumption	Quiescent current: 0.96W
General	IP rate	IP54
	Dimension (W x H x D)	140 x 134 x 33mm
	Shell material	PC+ABS
	Color	Blue
	Weight	185 g
Audio	Sound pressure	105 dB/30cm

ORDERING INFORMATION

114-508

Hikvision DS-PS1-B Wired Sounder Blue



Innovative Electronic Solutions
www.ness.com.au



NSW Ph 02 8825 9222
sales@ness.com.au

VIC Ph 03 9875 6400
nessmelb@ness.com.au

QLD Ph 07 3399 4910
nessbris@ness.com.au

WA Ph 08 9328 2511
nessper@ness.com.au

SA Ph 08 8152 0000
adelaide@ness.com.au