

DS-PHA64-LP/NP
AX Hybrid Pro control panel

114-500



AX Hybrid Pro control panel is a wired intrusion control panel with wireless detectors & peripherals access capability. It is the first control panel that supports Speed-X bus, which is a creative technology and is used to transmit verification video/picture from PIR-CAM. Besides, this hybrid control panel supports customized voice library, which is designed for users to upload customized voice files. These voice files will be played via alarm phone call when alarm triggered. As for basic functions, it supports Wi-Fi, TCP/IP and GPRS/3G/4G communication methods. It also supports Hik-ProConnect, Hik-Connect, Hik IP Receiver, Hik IP Receiver Pro and Hik-Central, which is applicable to the scenarios of market, hotel, supermarket, warehouse, office, house (especially with cables pre-installed), etc.

- Hybrid system: 8 on-board zones and 56 wired/wireless zones expandable; 4 on-board outputs (2 relay outputs & 2 I/O outputs) and 60 wired/wireless outputs expandable
- Dual-path communication of alarm events and other signals over LAN, PSTN, Wi-Fi, GPRS or 3G/4G utilizing a main and backup channel with configurable priority
- 4-ch onboard IP Camera video verification, supports video recording (5s pre-alarm + 2s post-alarm, or 2s pre-alarm + 5s post-alarm) for verification to the alarm receiving email or mobile client
- Supports arming/disarming via keypad, keyfob, mobile client, iVMS-4200, SMS and tag
- Pushes alarm notification via messages and Hik-Connect
- Supports ISAPI, Cloud P2P, ISUP, CSV-IP and DC-09 protocol
- Supports 1 Speed-X BUS

▪ Specification

Software features	
Zones	64 (8 On-board zones, max 8 wired PIRCAM)
Area	32
User	Installer: 1 Administrator: 1 Operator: 62
SMS notification	Support (with GPRS/3G/4G module)
Onboard video clips	4
ARC protocol	ISAPI: Supports iVMS-4200 client software and web client Cloud P2P: Supports cloud P2P privacy protocol DC-09: ARC accessible (ADM-CID/SIA-DCS) CSV-IP: Supports CSV-IP ISUP: Supports ISUP 5.0
Programming tools	Web/iVMS-4200/Hik-ProConnect/Keypad
Firmware upgrade	Web/iVMS-4200/Hik-ProConnect/Hik-ProConnect
End of Line Resistance	Support 2.2K, 5.6K, 8.2K
Hardware features	
Alarm input	64 (Including 8 on-board zones)
Alarm output	64 (Including 2 on-board relay outputs and 2 on-board I/O outputs)
Power Output	12V 1.5A
3/4G on board	Optional
GPRS on board	Optional
Wi-Fi	802.11b/g/n (2.4GHz)
Bus	1 Speed-X bus
Sounder output	1 Wired on-board sounder output
Tamper-Proof	1 switch to detect removal from mounting 1 switch to detect front cover open
Network interface	1 RJ45 10M/100M Ethernet interface
Electrical characteristics	
Power interface	12 - 15V DC
Power Consumption	1. 220V power supply ① With an alarm: 2A, 32W ② Without an alarm: 250mA, 4W 2. 13.5V battery supply ① With an alarm: 1.7A, 25W ② Without an alarm: 200mA, 2.7W
Battery type	Lead acid battery (12V 7Ah, battery is not included by default)
Storage temperature	-10°C to 40°C
Battery life span	Up to 36hrs

Display	
Indicator	4 On-board LEDs 1. 1 AC power LED indicator (Green) 2. 1 System status LED indicator (Green/Red) 3. 1 PSTN status LED indicator (Green/Red) 4. 1 Mobile communication status LED indicator (Green/Red)
General	
Operation temperature	-10°C to 40°C
Operation humidity	10% to 90%
Shell material	Plastic
Color	White
Dimension(WxHxD)	261 mm × 199 mm × 86.4 mm
Weight	997 g
Device management	
Tag	64
Keyfob	64
Keypad	8
Wireless sounder	16

ORDERING INFORMATION

114-500 Hik DS-PHA64-LP/NP AX Hybrid Pro Panel only



Innovative Electronic Solutions
www.ness.com.au



NSW Ph 02 8825 9222
sales@ness.com.au

VIC Ph 03 9875 6400
nessmelb@ness.com.au

QLD Ph 07 3399 4910
nessbris@ness.com.au

WA Ph 08 9328 2511
nessper@ness.com.au

SA Ph 08 8152 0000
adelaide@ness.com.au