

DS-PSG-WO Wireless Outdoor Siren

K-114-203

The wireless outdoor siren is used to connect to security control panel for instant notice when an alarm is triggered.



Key Feature

- 433/868 MHz two-way wireless communication
- Reports exception automatically
- AES-128 encryption
- Adjustable volume: low, medium, and high
- Front and rear panel tamper-proof
- Protection level: IP65
- Outdoor installation
- Flashing blue LED for alarm indication
- 3 kinds of alarm sounds: fire alarm, intrusion alarm, and panic alarm

Specifications

Model	DS-PSG-WO-433/DS-PSG-WO-868	
RF	RF frequency	433/868 MHz
	RF modulation	2GFSK
	RF speed	10 kbps/4.8 kbps
	RF power	10 dBm
	RF method	Two-way communication
	RF encryption	AES-128
	RF distance	800 m (open area)
Electrical & battery	Power	4 CR123A Batteries (default) or 12 VDC
	Consumption	Static consumption: < 20 uA
	Battery life span	5 years in stand-by status
Interface and component	Learnt button	1
	TAMPER switch	Front and rear panel tamper-proof
	Indicator	Blue (on front panel), Green/Red (on PCB)
	Buzzer	1, Decibel: 110 dB
Others	Operation temperature	-25 °C to +60 °C (-13 °F to +140 °F)
	Operation humidity	10% to 90% (no condensing)
	Color	White and blue
	Material	PC+ABS
	Dimension (W × H × D)	220.5 × 205.2 × 46 mm (8.68" × 8.08" × 1.81")
	Protection level	IP65
	Installation	Wall mounting

ORDERING INFORMATION

K-114-203 Hikvision DS-PSG-WO-433 W/BATTERIES



Innovative Electronic Solutions
www.ness.com.au



NSW Ph 02 8825 9222
sales@ness.com.au

VIC Ph 03 9875 6400
nessmelb@ness.com.au

QLD Ph 07 3399 4910
nessbris@ness.com.au

WA Ph 08 9328 2511
nessper@ness.com.au

SA Ph 08 8152 0000
adelaide@ness.com.au