

DS-PM1-O1H-WB
Wireless Wall Switch

114-270



- 433MHz two-way wireless communication
- AES-128 encryption
- LED display, show status of device and replay on/off display
- Small case design, which can be put into hiding places easily
- Automation operating, one button turn on/off from APP/Keyfob/Keypad
- Setting scenarios by different events

Specifications

Model		DS-PM1-O1H-WB
Software features	Learning Button	1, For register
	Scenario Setting	By Alarm, By Operation, By Fault, By Schedule, By Manual
Hardware features	Relay output	1, NO/NC (AC 100 to 240v, Max. 13A)
	Serial port	1, for debug
Electrical characteristics	Power supply	AC 100v to 240v, 50/60 HZ
Display	LEDs Status	3, Register/Signal (Green/Red), Power (Green), Relay Status (Blue)
General	Operation temperature	-10 °C to +55 °C (14 °F to 131 °F)
	Operation humidity	10% to 90%
	Shell material	Plastic
	Dimension(W xHxD)	38x25x18mm
	Weight	31.5g
	Color	White
	Installation method	Wall Mounting or Inside 86 box

ORDERING INFORMATION

114-270

Hikvision AX PRO Series Wall Switch



Innovative Electronic Solutions
www.ness.com.au



NSW Ph 02 8825 9222
sales@ness.com.au

VIC Ph 03 9875 6400
nessmelb@ness.com.au

QLD Ph 07 3399 4910
nessbris@ness.com.au

WA Ph 08 9328 2511
nessper@ness.com.au

SA Ph 08 8152 0000
adelaide@ness.com.au